

Cable PUR 1x M12 Female 8p
Cable
M12 to open ended wires
PUR
8x0.25 mm²
M12 Female 8-pole
straight
various lengths




Cable PUR 1x M12 Female 8p
Cable
Jacket
Jacket material
Jacket color
Outer diameter
Wires
Wire isolation
Number of wires
Wire diameter
Wire colors
End of wires
Shielding
Twisted pairs
Connector
Size
Number of poles
Mounting
Length
Lengths
Length tolerance
Temperature range
Fixed
Flexible
Certifications
UL Listed
Electrical data
Voltage rating
Impuls voltage rating
Current rating
Environmental
Resistance
Chemical
Oil resistance
UV resistance


General specifications v20150706	
Li9Y11Y	
PUR	
grey	
ø 6,0 mm ±5%	
PP	
8	
0.25 mm ² (AWG 24)	
white, brown, green, yellow, grey, pink, blue, red (DIN colors)	
stripped	
no	
no	
M12	
female, A-coding	
8	
moulded, straight	
1,5m / 5m / 10m / 15m / other lengths on request	
1.5m: +0.1m / other lengths: ±1.5%	
-40° ... +80°C	
-20° ... +80°C	
no, optional available	
max. 30V AC/DC	
0,8 KV	
max. 2A every contact	
material resistance should always be checked in the application involved	
good chemical resistance	
yes	
standard	

Cable PUR 1x M12 Female 8p
Connection
Wire / pin coding


Connectivity	
M12 connector: 1x female (8 pins, A-coding)	
Pin 1:	White
Pin 2:	Brown
Pin 3:	Green
Pin 4:	Yellow
Pin 5:	Gray
Pin 6:	Pink
Pin 7:	Blue
Pin 8:	Red



Cable PUR 1x M12 Female 8p



Cable PUR 1x M12 Female 8p
2: cable sleeve
3: cable
L: length (various)



Cable PUR 1x M12 Female 8p

DIS Ordering codes	
Order code	Description
11706	1,5m length cable PUR with 1x M12 Female 8p
11707	5m length cable PUR with 1x M12 Female 8p
11708	10m length cable PUR with 1x M12 Female 8p
11709	15m length cable PUR with 1x M12 Female 8p
	other lengths on request